

PRODUCT DATA

ROLL LENGTH / WIDTH: 20m x 1m

ROLL THICKNESS: 3mm, 4.5mm & 5mm

M2 WEIGHT: 3mm = 2.05 Kgs / 5mm = 3.62 Kgs

COLOUR: BLACK / BEIGE

SURFACE: FINE GRANULATE STRUCTURE

TENSILE STRENGTH: 0.6 N / mm² (DIN 53571)

ELONGATION AT BREAK: 3mm APPROX 50% (DIN 53571) 5mm APPROX 60% (DIN 53571)

DENSITY: APPROX 390 kg/m³

SERVICE TEMP: -30°C TO +80°C

FLAMMABILITY RATING: B2

ENVIRONMENTAL BEHAVIOUR: LIMITED RESISTANCE TO ACID

IMPACT SOUND: 5mm = 21dB, 3mm = 18dB

FEATURES

EASY TO INSTALL.

REMAINS CONTINUALLY ELASTIC.

FULLY RECYCLED.

MINIMUM CONSTRUCTION HEIGHT.

SUITABLE TO BE LAID OVER BOTH CONCRETE AND SCREEDED FLOORS.

COMPLIES WITH ALL UK BUILDING REGULATION STANDARDS. INCLUDING DOCUMENT E (ENGLAND & WALES), SECTION 5 (SCOTLAND) AND PART G (NORTHERN IRELAND).

SUITABLE FOR REFURBISHMENT / NEW BUILD.

FOR USE WITH UNDER FLOOR HEATING.

EXCELLENT THERMAL PROPERTIES.

EXCELLENT FOOTFALL NOISE REDUCTION.

CAN BE USED AS PART OF A CODE FOR SUSTAINABLE HOMES COMPLIANT SPECIFICATION.

CAN BE USED AS AN ALTERNATIVE PRODUCT FOR ROBUST DETAILS SPECIFICATIONS.

HUSH UNDERLAY FOR VINYL FLOORING CAN ALSO BE USED UNDER:

CERAMIC TILE, SHEET VINYL, STONE FLOORS, LAMINATE, WOOD FLOORS, PARQUET, CARPET, FLOTEX, MARBLE FLOORS.

