

**PRODUCT DATA**

**ROLL LENGTH / WIDTH: 20m x 1m**

**ROLL THICKNESS: 3mm, 4.5mm & 5mm**

**M2 WEIGHT: 3mm = 2.05 Kgs / 5mm = 3.62 Kgs**

**COLOUR: BLACK / BEIGE**

**SURFACE: FINE GRANULATE STRUCTURE**

**TENSILE STRENGTH: 0.6 N / mm<sup>2</sup> (DIN 53571)**

**ELONGATION AT BREAK: 3mm APPROX 50% (DIN 53571) 5mm APPROX 60% (DIN 53571)**

**DENSITY: APPROX 390 kg/m<sup>3</sup>**

**SERVICE TEMP: -30°C TO +80°C**

**FLAMMABILITY RATING: B2**

**ENVIRONMENTAL BEHAVIOUR: LIMITED RESISTANCE TO ACID**

**IMPACT SOUND: 5mm = 21dB, 3mm = 18dB**

**FEATURES**

**EASY TO INSTALL.**

**REMAINS CONTINUALLY ELASTIC.**

**FULLY RECYCLED.**

**MINIMUM CONSTRUCTION HEIGHT.**

**SUITABLE TO BE LAID OVER CONCRETE, SCREEDED AND TIMBER FLOORS.**

**COMPLIES WITH ALL UK BUILDING REGULATION STANDARDS. INCLUDING DOCUMENT E (ENGLAND & WALES), SECTION 5 (SCOTLAND) AND PART G (NORTHERN IRELAND).**

**SUITABLE FOR REFURBISHMENT / NEW BUILD.**

**FOR USE WITH UNDER FLOOR HEATING.**

**EXCELLENT THERMAL PROPERTIES.**

**EXCELLENT FOOTFALL NOISE REDUCTION.**

**CAN BE USED AS PART OF A CODE FOR SUSTAINABLE HOMES COMPLIANT SPECIFICATION.**

**CAN BE USED AS AN ALTERNATIVE PRODUCT FOR ROBUST DETAILS SPECIFICATIONS.**

**HUSH UNDERLAY FOR VINYL FLOORING CAN ALSO BE USED UNDER:**

**CERAMIC TILE, SHEET VINYL, STONE FLOORS, LAMINATE, WOOD FLOORS, PARQUET, CARPET, FLOTEX, MARBLE FLOORS.**

