



PP8 STRAP HANGERS @ MAX 1200 C/CS CONNECTED TO PP7 WITH 2ND. STEEL FRAMING SCREWS REF G236; FIXED TO TIMBER JOISTS VIA PP12 BRACKETS OR PP13 OR 14 ACOUSTIC BRACES, CONNECTED BY PP11 NUT & BOLT SECURED TO JOISTS BY MIN 40MM X NO 6 WOODSCREW (OR SIMILAR)
NOTE: AT LEAST 35MM OF SCREW MUST PENETRATE TIMBER

HUSH-SLAB SOUND ABSORBER 100MM THICK LAID OVER PP5'S BETWEEN PP7'S

12.5MM FERMACELL BOARD SCREWED TO PP5'S AT MAX 230 C/CS;
10MM FERMACELL BOARD SCREWED TO 1ST LAYER LAYER BOARD @ MAX 230 C/CS;
BOTH LAYERS FIXED USING FERMACELL 3.9 X 30MM SCREWS

PP7 PRIMARY SUPPORT CHANNELS
● MAX 1200 C/CS

PP6 PERIMETER CHANNEL SECURED TO WALL ● 600 C/CS

PP9 CONNECTING CLIP

PP5 'TOP HAT' CHANNELS
● MAX 500 C/CS