

ACOUSTIC PERFORMANCE

FREQUENCY (Hz)	125	250	500	1000	2000	4000	NRC	CLASS
12mm ASPECT	0.05	0.10	0.40	0.75	0.95	1.00	0.55	D
12mm ASPECT (with 25mm air gap)	0.10	0.30	0.75	1.00	1.00	1.00	0.75	C
24mm ASPECT	0.10	0.30	0.75	1.00	1.00	1.00	0.75	C
24mm ASPECT (with 25mm air gap)	0.15	0.45	0.95	1.00	1.00	1.00	0.85	C

ASPECT™ IS SPECIFICALLY DESIGNED TO REDUCE AND CONTROL NOISE REVERBERATION IN BUILDING INTERIORS.

MINIMUM NOISE REDUCTION COEFFICIENT 0.55

PRODUCT SPECIFICATIONS

PRODUCT NAME: ASPECT™

COMPOSITION: 100% POLYESTER FIBRE (PET)

PANEL DIMENSIONS: 1220mm x 2440mm

WEIGHT: 2400gsm / 4800gsm

DENSITY: 200kg/m³

INSTALLATION

INSTALL AS PER VIVID ACOUSTICS RECOMMENDATIONS.

FASTNESS TO LIGHT

ASPECT™ IS SUITABLE FOR INDOOR USE ONLY.

THERMAL PERFORMANCE

ASPECT™ 12mm R0.41 (@15°C)

ASPECT™ 24mm R1.82 (@15°C)

FIRE RATINGS

EN13501-1:2007+A1:2009 B - s1, d0

MOISTURE ABSORPTION

POLYESTER IS NOT AFFECTED BY MOISTURE, MOULD OR MILDEW AND WILL NOT ROT OR DETERIORATE IN APPLICATIONS.

PATTERN REPEAT

ZERO PATTERN REPEAT BUT PRODUCT HAS DIRECTIONAL GRAIN.

FABRIC CARE

CLEANING GUIDE AVAILABLE UPON REQUEST.

ENVIRONMENTAL

VIVID ASPECT IS MANUFACTURED USING 100% POLYESTER FIBRE AND CONTAINS A MINIMUM OF 70% POST-CONSUMER RECYCLED PET (PLASTIC BOTTLES).

COLOUR OPTIONS

CRYSTAL / SMOKED TOPAZ / TOPAZ / MORION / JET / SAPPHIRE / CITRINE / SIAM OPAL / OLIVINE.

